

INS-8005E

Premium Unmanaged 5 x 10/100 RJ45 Industrial Switch

Description

INS-8005E is an unmanaged industrial Fast Ethernet switch with 5 auto-negotiation 10/100 Mbps downlink ports to expand Ethernet networks in factory floors and for high demanding environments with complex networks and limited space.

The switch offers various in-built traffic optimization and network performance features to prioritize important industrial data packets, prevent the loss of data during communication, and stable transmission; like flow and storm control and VLAN Passthru. It prioritizes industrial protocols for industrial applications, like Ethernet/IP, PROFINET, and GOOSE packets. Additionally, it offers per-port and 802.1p Tag Quality of Service to ensure the delivery of high priority data.

This networking device is built with industrial grade components to protect it from hazards like vibration, shock, free fall, interference, and extreme temperatures that make it resistant to harsh industrial environments.



RoHS **CE** **FCC** **UL LISTED**



Features Highlight

Ruggedized Components Designed for Harsh Industrial Environments

Built with industrial-grade components, good thermal conductivity, and enclosed in an IP40 metal case, this Ethernet switch is resistant to extreme environments, vibration, EMI (electromagnetic interference), ESD (electrostatic discharge), power surge, over-voltage, over-current, and reverse polarity. It withstands operation at extreme temperatures between -40°C~75°C (-40°F~167°F). It follows international safety standards like CE, FCC, and ROHS for safe operation.



Quick and Convenient Installation with Auto-negotiation


INS-8005E works as soon as it is connected and makes installation convenient. One 12~48VDC power supply connects to the 3-pin terminal block for power. The 10/100 Mbps ports use auto MDI/MDI-X connection for auto-negotiation to work as soon as connected to other network devices at the required speed without extra software installation needed. The LED light displays when the device is in operation. The slim and small design allows it to fit at different locations for many devices to operate in the same network and can be mounted to a standard TH35 DIN rail.

Traffic Control Mechanisms to Optimize Bandwidth Usage

Traffic control mechanisms regulate excessive traffic to avoid delay, data loss and connection issues between devices. This unmanaged switch offers mechanisms such as Flow and Storm Control that prevent devices from overwhelming each other during the exchange of data and to keep the flux at a tolerable rate, hence keeping devices working within their capacity and avoiding the network from collapsing.

Intelligent VLAN Data Forwarding


INS-8005E is aware enough to read the source and destination of VLAN tagged data packets. This unmanaged switch delivers VLAN packets without changing or dropping them assuring operational data in industrial fields is delivered safely across devices.



Features Highlight


Critical Data Transmission Priority

INS-8005E streamlines the execution of time-sensitive applications with the 802.1p Tag QoS by classifying data into high and low priority. Additionally mission-critical applications in industrial automation like manufacturing and monitoring can be done without delay through port priority on port #1 even during high traffic.




Prioritizes Industrial Standard Protocols

Industrial automation applications employ packet protocols that focus on delivering data under tight time constraints. This unmanaged switch is configured with iQoS to prioritize industrial application protocols and deliver time-sensitive data used in industrial applications first, including Ethernet/IP, PROFINET, and GOOSE (Generic Object Oriented Substation Events).




Connects Large Network Groups and Facilitates Data for Monitoring Systems

During the network discovery process device flapping issue can be occurred when the peripheral devices are connected to an unmanaged switch in the network. The Link Layer Discovery Protocol (LLDP) Filter blocks the LLDP packets exchange at unmanaged devices only without disturbing managed groups to avoid the device flapping issue. However, the LLDP works well It provides precise device information and avoids false alarms in your network.



Applications

The INS-8005E is compatible with 10/100Mbps through RJ45 transceivers to guarantee a strong, stable connection of Ethernet, Fast Ethernet, as an ideal solution for deployment in multiple high-speed automation systems.



Specifications

Standards	
IEEE 802.3	10BASE-T
IEEE 802.3u	100BASE-TX
IEEE 802.3	Nway Auto-negotiation
IEEE 802.3x	Flow Control
IEEE 802.1p	Class of Service
Interface	
Ports	5 x 10/100BASE-TX (RJ45)
LED Panel	PWR, 100, LNK/ACT
Features	
Performance	Jumbo Frame size: 9216 Bytes
	MAC Table size: 2K
	Throughput: 14,880 pps to 10 Mbps ports
	148,800 pps to 100 Mbps ports
Switch Fabric	1Gbps
Forwarding Rate	0.74Mpps
Functions	LLDP Filter, Flow Control, VLAN Passthru, Port Priority (Port 1), 802.1p CoS/QoS, Storm Control, iQoS (EIP/PROFINET/GOOSE QoS)
Power	
Input Voltage	12~48VDC
Connector	Terminal block
Max Power Consumption	3W
Reverse Polarity Protection	Present
Over Load Protection	Present
Mechanical and Environment	
Housing	Aluminum (IP40 Protection)
Mounting	DIN-Rail, Wall Mount
Operating Temperature	-40°C~75°C (-40°F~167°F)
Storage Temperature	-40°C~85°C (-40°F~185°F)
Operating Humidity	5 to 95% RH (non-condensing)
Storage Humidity	5 to 95% RH (non-condensing)
Weight	183.4g
Dimension (WxHxD)	23.6 x 109.2 x 73.8 mm (0.93 x 4.3 x 2.90 in)

Standards and Certifications		
CE	EMI	FCC Part 15 Subpart B Class A EN 55011 / BS EN 55011 Class A EN 55032 / BS EN 55032 Class A EN 61000-6-4 / BS EN 61000-6-4
	EMS	EN 55035 / BS EN 55035 EN 61000-6-2 / BS EN 61000-6-2 EN 61000-4-2 (ESD) EN 61000-4-3 (RS) EN 61000-4-4 (Burst) EN 61000-4-5 (Surge) EN 61000-4-6 (CS) EN 61000-4-8 (PFMF)
Shock		IEC 60068-2-27
Freefall		IEC 60068-2-31
Vibration		IEC 60068-2-6
Safety		UL 61010-1, UL 61010-2-201
Ordering Information		
INS-8005E		Premium Unmanaged 5 x 10/100 RJ45 Industrial Switch
Optional Accessories		
Power Supplies		SDR-120-48: 120W DIN-Rail 48VDC Industrial Power Supply, -25°C~70°C (68°F~158°F)

Note:

* The highest degree of temperature operation certified by UL is -40°C~75°C (-40°F~167°F).

* Specifications subject to change without notice.

Dimension

